

## VOIP PHONE SNOM 360

The Next Generation of VoIP Phones



- Tilttable graphical display (128x64 pixels)
- 47 keys, 13 LEDs
- 12 programmable function keys
- Speakerphone
- 2x IEEE 802.3 10/100 Mbps switch
- Power over Ethernet
- Headset connection
- Expansion module with 42 programmable function keys
- SIP RFC3261
- Security: SIPS/SRTP, TLS
- STUN, ENUM, NAT, ICE
- Codecs: G.711, G.729A, G.723.1, G.722, G.726, GSM 6.10 (full rate)
- National Language Support
- XML driven mini-Browser

### → Usability

The snom 360 is designed for maximum productivity and efficiency in the everyday business environment. Dedicated keys provide you with direct access to the functions for audio and call control, and context-sensitive menus offer you the additional functionality that you may need at any given moment. The graphical display can be tilted for your optimum reading angle.

Additional sophisticated call control features, full call detail, configuration options can be accessed via web browser. Customized ring tones can easily be downloaded from the web server – including, of course, your favorite ring tone. Incoming calls can be marked with special ring tones to indicate the destination of the call.

### → Security

12 programmable keys can be used to customize the functionalities according to your own specific needs. The LED associated to a function key shows you whether or not your colleague is currently on a call. And, of course, your colleagues can see whether your line is free or not.

The new mini browser, embedded in snom's top-of-the-line 360 executive SIP phone, lets users and developers create web-driven, screen-based telephone applications. Examples include custom contact-center apps, web-based phone directories, messaging, posting of news and other info on telephone screens, and more.

### → Interoperability

To spare you the annoyance of unwanted invasions of your speech data, the snom 360 supports the security standard SRTP – a current specification from the Internet Engineering Task Force (IETF) for protection against eavesdropping and the stealing of data.

With SIP (Session Initiation Protocol) you are ensuring your own personal independence. Most vendors are touting SIP to be the communication protocol of the future. SIP components can be combined into a complete system without you being tied to a single provider.

# TECHNICAL DATA SNOM 360

## GENERAL FEATURES

- **Dimensions:** approx. 25x20x13 cm
- **Weight:** approx. 960 g
- **Safety:** IEC 60950-1:2001, CB Test Certificate: DE 2-008417
- **Certifications:** FCC Class B, CE Mark
- **Power consumption:** 2.2–2.5 watts

## CONNECTORS

- **1 x LAN, 1 x PC:** RJ45 (Ethernet)
- **Power:** 5 V DC
- **Ethernet:** 2 x IEEE 802.3 10/100 Mbps switch
- **Power over Ethernet:** IEEE 802.3af, Class 1
- **Handset:** RJ11 connector
- **Headset:** RJ11 connector
- **Expansion Module:** Proprietary snom connector

## USER INTERFACE

- 128x64 pixels, tiltable graphical display, backlit
- 47 keys, 12 programmable function keys with LEDs (54 with the expansion module)
- Caller-ID
- Message waiting indication LED
- Address book (100 entries)
- Address book import/export
- Speed dialing
- Local dial plan
- Number guessing
- Lists of missed, received and dialed calls (100 entries each)
- Call waiting indication
- Clock, daylight saving, call-timer
- Call blocking (deny list)
- Blocking of anonymous calls
- Handling of up to 12 calls simultaneously
- Menu-driven user interface
- Ring tone selection, import of individual ring tones
- URL Dialing support

- National language support for selected languages (NLS)
- Do not disturb
- Speakerphone (full duplex)
- Auto answer mode
- Keyboard lock

## CALL FEATURES

- Hold
- Blind transfer, attended transfer
- Music-on-hold support (only via PBX)
- Divert
- Conferencing (3-way conference bridge on phone)
- Call park, call pickup (only via PBX)
- Call completion
- Client Matter Code (CMC)
- Call waiting/switching between calls
- Redialing
- RTP multicast paging
- Multiple audio device support

## WEB SERVER

- Embedded web server HTTP/HTTPS
- Easy configuration of the phone, remote configuration
- Dial from web interface
- Password protection
- Diagnostics (tracing, logging, syslog)

## SECURITY, QUALITY OF SERVICE

- HTTPS (server/client)
- Transport Layer Security (TLS)
- SRTP (RFC3711), SIPS
- RTCP
- VLAN (802.1 pq)

## CODECS, AUDIO

- G.711 A-law,  $\mu$ -law
- G.729A, G.723.1, G.726
- GSM 6.10 (full rate)
- G.722
- Comfort noise, voice activity detection

## SIP

- RFC3261 compliance
- UDP, TCP and TLS
- Digest/basic authentication
- Loose routing and strict routing support
- PRACK (RFC3262)
- Error-information support
- Reliability of provisional responses (RFC3262)
- Early media support
- DNS SRV (RFC3263), redundant server support
- Offer/answer (RFC3264)
- Message Waiting Indication (RFC3842), subscription for MWI events (RFC3265)
- Dialog-state monitoring (RFC 4235)
- In-band DTMF/out-of-band DTMF/SIP INFO DTMF
- STUN client (NAT traversal)
- ENUM (RFC3261), NAPTR (RFC2915), rport (RFC3581), REFER (RFC3515)
- Event list subscription support (RFC4662)
- Bridged line appearance (BLA)
- Auto provisioning with PnP
- Presence/buddylist feature
- Busy lamp field support (BLF)
- Presence publishing

## INSTALLATION

- Automatic software update
- Automatic settings retrieval via HTTP/HTTPS/TFTP
- Installation via web interface
- Static IP provisioning, DHCP
- NTP

For more information, please contact your snom partner.

Version 1.2 / 15 Feb 2008  
 Copyright © 2000–2008 snom technology AG. All rights reserved. snom is a registered trademark of snom technology AG and affiliates in Germany, USA and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, in this document are legally protected trademarks of snom technology AG. Other trademarks or registered trademarks mentioned in this document are the property of their respective manufacturers or owners. Product specifications contained in this document are subject to change without notice.

snom technology AG

Charlottenstraße 68-71  
 10117 Berlin  
 Germany  
 tel/enum: +49 30 39833-0  
 fax: +49 30 39833-111  
 sip: info@snom.com  
 mail: info@snom.com

[www.snom.com](http://www.snom.com)